

TRUESHIELD™ HERO™

PRODUCT TECHNICAL DETAILS & OPTIONS

APPLICATION:

- CP Rectifier Equipment

WIRELESS NETWORK:

- Digital Cellular 4G, 3G, 2G Compatible
- Global Satellite (Iridium)

SPECIFICATIONS:

- **Size:** 14H" x 12D" x 6"
- **Weight:** 14 pounds
- **Power requirement:** 115/230 VAC
- **Inputs:**
 - Rectifier Output Voltage
 - 0-150 VDC
 - DC Shunt Voltage: 0-500 mVDC
 - Aux: 0-4 VDC
- **Battery Voltage:** 12 VDC
- Battery Back-up
- **GPS-Synchronized Interrupt:**
 - Sub Second or Longer
- **RF Power:** 3 Watts
- **Antenna:** 3db Enclosure Mount
- **Temp:** -20°C to +70°C



FEATURES:

- GPS-Synchronized Rectifier Interruption
- StormSense™ Lightning Protection
- OmniUpdate™ Remote Firmware Update
- Wireless to Web Enabled
- OmniView®, Secure Interactive Website
 - Featuring ScopeView™
- Programmable Reporting Interval and Alarm Limits
- Superior Battery Maintenance
- NEMA 4X Enclosure
- Tamper Indication
- Optional Multiplexor (Measures Multiple Bonds)
- All Configuration Done Remotely
- No Field Laptop Required/No Custom Software



www.omnimetrix.net
770.209.0012 | info@omnimetrix.net